

TC-C34HN 4MP H.265 IR Dome Camera(2.8mm)


4MP H.265 IR Dome Camera(2.8mm)



Features

- Semi metal housing
- Up to 2560*1440
- S+265/H.265/H.264 Codec
- Min. Illumination Color: 0.05 Lux,B/W: 0.01Lux,0 Lux with IR
- Smart IR, IR Range: 30m
- Operating Conditions -35℃~65℃(IR OFF) /-35℃~-40℃(IR ON), 0~95% RHG
- PoE, IP66
- 3 Smart features:
Smart alarm, an advanced motion detection to recognize only human among all the moving objects.
Smart codec, 256kbps for 1080P video stream and 1GB storage for 24 hours recording.
Smart image, an advanced algorithm to make sure to see human clearly.

Dimensions



Tiandy

Camera	
Image Sensor	1/2.7" CMOS
Signal System	PAL/NTSC
Min. Illumination	Color: 0.05Lux ; B/W: 0.01Lux
Shutter Time	1s to 1/100,000s
Lens	2.8mm
Lens Mount	M12
Day& Night	IR Cut Filter with Auto Switch
Wide Dynamic Range	100dB
Digital Noise Reduction	3D DNR
Compression Standard	
Video Compression	Smart S+265/S+265/H.265/S+264/H.264
Video Bit Rate	32Kbps~6Mbps
Audio Compression	N/A
Audio Bit Rate	N/A
Image	
Max. Image Resolution	2560x1440
Frame Rate	PAL: 1440P@15fps, 2304*1296@25fps, 1080p@25fps, 960P@25fps, 720P@25fps NTSC: 1440P@15fps, 2304*1296@30fps, 1080p@30ps, 960P@30ps, 720P@30ps
Mainstream	1440P(2560x1440)
Substream	4CIF (704x480)
3rd Stream	N/A
Image Settings	Brightness, Saturation, Contrast,Flip Mode Adjustable by Client Software or Web Browser
HLC	Y
Smart Defog	Y
Corridor Format	N/A
ROI	N/A
Privacy Mask	Y
Picture Overlay	N/A
OSD	16x16, 32x32, 48x48 Size Letters Such as Week, Date, Time, Total 1 Regions
Network	
Network Storage	N/A
NTP	Y
ANR	N/A
Video Analytics	N/A
EW	N/A
Alarm Trigger	Advanced Motion Detection/IP Conflict/MAC Conflict
Protocols	TCP/HTTP/MULTICAST/UPnP/DDNS/FTP/NTP/RTSP/S/MTP/
Remote Connection	Y
System Compatibility	ONVIF (Profile S)
Smart Feature	
smart alarm	Y. An advanced motion detection to recognize only human among all the moving objects.
smart codec	Y. 256kbps for 1080P video stream and 1GB storage for 24 hours recording
smart image	Y. An advanced algorithm to make sure to see human clearly.
Interface	
Audio Input	N/A
Audio Output	N/A
Communication Interface	1-ch RJ45 10M / 100M Ethernet Interface
Alarm Input	N/A
Alarm Output	N/A
Video Output	N/A
On-board Storage	N/A
Extension	N/A
General	
Language	English,Simplified Chinese,Traditional Chinese,Spanish, Italian, Korean, Turkish, Russian, Thai, polish, French
Operating Conditions	-35℃~65℃, 0~95% RHG
Power Supply	DC 12 V ± 20%, POE
Power Consumption	MAX 6W (POE) , MAX 6W (DC12V)
IR Light	1
IR Distance	30m
White Light	N/A
Impact Protection	IP66

Dimensions	115mm (diameter) × 97mm (height)
Weight	0.6KG